



ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, German language, 200/240 V and German power cable




Similar Image

ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, German language, 200/240 V and German power cable

- Frictionless ACP dry pump with 25 m³/h backing capacity
- 20 l/s helium pumping speed
- 200/240 V operating voltage
- German power cable
- Voice synthesizer in German
- Remote control in mbar l/s

Dimensions



Technical Data

ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, German language, 200/240 V and German power cable

Backing pump	with oil free backing pump
Backing pump capacity	25 m ³ /h
Detectable gases	⁴ He
Dimensions (L x W x H)	594 x 692 x 933 mm
Flange (in)	DN 50 ISO-KF
I/O interfaces	Digital inputs (Start, Vent, Calibration...); Digital outputs (Test modes, cycle in progress, helium signal above reject set point...); Analog outputs (Helium signal log, Inlet pressure)
Interface	RS-232
Language	German

Technical Data		ASM 192 T2D+, 25 m³/h, remote control in mbar l/s, German language, 200/240 V and German power cable
Mains cable		German power cable
Max. inlet test pressure		30 hPa
Minimum detectable leak rate for helium (sniffing leak detection)		1 · 10 ⁻⁸ Pa m ³ /s
Minimum detectable leak rate for helium (vacuum leak detection)		5 · 10 ⁻¹³ Pa m ³ /s
Noise level		66 dB(A)
Operating temperature		10 - 40 °C
Pumping speed for He		20 l/s
Start-up time (20°C) with calibration		5 min
Start-up time (20°C) without calibration		3,5 min
Supply		200-240 V, 50/60 Hz
Test method		Vacuum and sniffing leak detection
Type		High Performance - Console
User interface		Graphic color touch screen
Weight		157 kg 346.12 lb

Order number	
ASM 192 T2D+, 25 m ³ /h	D30R0S0MC860

Accessories	
Helium spray gun	
Helium spray gun, standard	112535
Helium spray gun "Elite-Kit", spray gun with additional accessories in a compact case	109951
Sniffer probe	
Sniffer probe, 5 m hose length, flexible 15 cm nozzle	SNC1E3T1
Sniffer probe, 5 m hose length, rigid 9 cm nozzle	SNC1E1T1

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a
perfect vacuum solution?
Please contact us:

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

All data subject to change without prior notice.

PFEIFFER  **VACUUM**